

# Specifications

Model		GZD15-LD	GZD15-HD
<b>Engine</b>	Model	Kubota Z602	
	Fuel type	Diesel Liquid-cooled (2 cyl.)	
	Displacement	599 cc (36.5 cu. in.)	
	Power	11.2 kW (15 HP)	
	Fuel capacity	20 l	
	Battery	12V (450 CCA)	
	Alternator	15 Amps	
	<b>Tractor</b>	Mower position	Mid-Mount
Front axle pivot		Standard	
Type		4Wheels-2WD	
Tyre size Front/Rear		15×6.0-6 / 20.0×10-8	
Tread Front		770 mm	
Rear		950/850 mm 2 positions	
Wheel base		1285 mm	
Overall Length		2785 mm	
Overall Width		1200 mm	
Overall Height		1115 mm	1345 mm
Weight (w/mower & GC)		510 kg	540 kg
<b>Drive Train</b>		Speed Front/Rear	0-13.5 km/h / 0-10 km/h
	T/M drive system	Shaft drive	
	Mower drive system	Shaft drive	
	Drive system	2-HST	
	Steering style	2-Hand Levers	
	Parking brake	Wet multi-discs, Mechanical equalising brake system	
	Turning radius	0 m	
	<b>PTO</b>	PTO clutch	Hydraulic Wet Multi Discs
PTO brake		Hydraulic Wet Single Disc	
<b>Mower</b>	Cutting width	42" (1067 mm)	
	Lift system	Hydraulic	
	Mount system	Parallel Linkage	
	Blade drive system	Hex belt, gear	
	Cutting height	1-4 in. (1/4"), 4-5 in. (1/2") (25-102 mm (6 mm), 102-127 mm (13 mm))	
	Cutting height adj.	Dial	
	Max. Mower lift height	135 mm	
	No. of blades	2	
<b>Grass Collector</b>	Type	Low dump/Hydraulic	High dump/Hydraulic
	Capacity	400 l	
	Lift height (MAX)	—	1.8 m (5.9 ft)

The company reserves the right to change the above specifications without notice.  
This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

©2006 Kubota Corporation



**KUBOTA (DEUTSCHLAND) GmbH**

Senefelder Straße 3-5, 63110 Rodgau/Nieder-Roden  
Telefon 06106/873-0 Telefax 06106/873-197 E-mail info@kubota.de  
[www.kubota.de](http://www.kubota.de)